

DT828L

Computerized Double Needle Lockstitch
Machine With Double Stepping Motor

雙步進雙針電腦平縫車

SIRUBA
銀箭牌



You Tube



YOUKU



- 上軸採用通軸設計，整體力矩輕，機器運轉平穩，送料流暢。
- 本機採用750W大功率伺服電機直接驅動，噪音低、振動小，安裝方便，啟動停車反應迅速，機針貫穿力強。
- 雙步進驅動技術，實現縫、加固、剪線和抬壓腳無聲。
- 密封式油盒設計，清潔無污染。
- 電子膝控裝置，抬壓腳輕盈省力，降低勞動強度。
- LED照明燈亮度三檔可調。
- 多鍵位操作面板，操作內容直觀，簡單方便。
- 一體式背掛式電控，安裝方便。

- The upper shaft adopts the through-all design; the overall torque is light; the machine runs smoothly; and the feeding is smooth.
- 750W high-power servo motor: larger needle penetration force, lower noisy, lower vibration, easier to install and shorter responding time.
- Stepping motor with bidirectional driven technique: powerful, stable as well as quiet when end back-tacking, reinforced stitching, trimming, and presser foot lifting.
- The sealed lubricate design: avoid fabrics from grease effectively.
- Electronic knee control pad makes the foot lifter light and easy to operate.
- 3-level LED light.
- Multi-functional panel: intuitive and user-friendly.
- Integrated back-mounted control box; easy to install.



KAULIN

特點

FEATURES

<p>角縫車縫 Split needle bar sewing</p> <p>一般車縫 General sewing</p>	<p>高品質的加固縫線跡：採用步進馬達控制的送料機構，精準控制送料行程，任何針距下都可以實現線跡重合的加固縫。</p>	<p>電子膝控：不改變工人的操作習慣實現輕鬆抬壓腳。</p>
<p>多功能按鍵設置：可以輕鬆實現轉角、倒縫、密縫、補針等縫紉。</p> <p>The multifunctional buttons: easy to achieve angle change, reverse stitch, seam stitch and stitch compensation.</p>	<p>High-quality reinforcement stitches: Step motor can accurately control the feeding, making reinforcement available for any stitch length.</p>	<p>Electronic knee pad: Without worker changing operating habits, presser foot can be easily lifted.</p>

- 1** 步進馬達雙向驅動技術 (專利技術): 一個馬達完成切線和抬壓腳動作。

可靠的切線機構:

切線機構採用步進馬達驅動，結構簡單、切線穩定、方便維護。

Stepping motor bidirectional driven technology (patent):

One step motor control trimming and pressing foot lifter work.

The unique thread trimmer device: Adopt step motor to drive, stable, light noise and convenience on maintenance.
- 2** 直刀剪線結構:

直刀剪線機構，剪線穩定。

Straight knife system:

Straight knife thread trimming mechanism, stable thread trimming.
- 3** 密封油盤設計:

縫料清潔無污染。

The sealed lubricate design:

Effectively avoid the material dirty from oil.
- 4** 多功能鍵操作面板:

操作盒按鍵內容直接，操作簡便迅速。

Multi-function key operation panel:

The operation box has direct key content, and the operation is simple and rapid.



規格

SPECIFICATIONS

DT828L	mm	Needle No. DP _x 5	布料厚度 Fabric Weight			mm		mm	S.P.M. (Max)	mm	KG
			L	M	H	手動 Hand	自動 Auto				
42	3.2 4.8 6.4	#11 - #16				7	8-12 (可調 Adjustable)	M: 0~4 H: 0~5	3000	L680 W290 H640	55 / 62
45								M: 0~4 H: 0~5			
72		#14 - #22						M: 0~7			
75								M: 0~7			

功能 Function	規格 Sub-Class	針送 Needle Feed	標準旋梭 Standard Hook	大旋梭 Big Hook	倒縫 Reverse Feeding	角縫 Split Needle Bar
	42	V	V	-	V	-
	45	V	V	-	V	V
	72	V	-	V	V	-
	75	V	-	V	V	V