

# OVERLOCK SEWING MACHINE

**747 L - 514 M - 3 - 2 4 / VT**

①線數  
Thread Numbers

737	: 3T
747	: 4T
757	: 5T
767	: 6T

⑥針距  
Needle Gauge

⑦包邊寬度  
Overedge Width

⑧配件  
Device

②機種別  
Model

L 基本型  
Basic Type

③縫合方式  
Sewing Types

503	
504	
505	
512	
514	
516	
644 (514+401)	

④車縫布料/上勾針縫容量  
Sewing Fabric/Upper Looper Capacity

F	輕薄布料 Fine Weight Fabric
L	薄布料 Light Weight Fabric
M	中厚布料 Medium Weight Fabric
H	厚布料 Heavy Weight Fabric
X	特厚布料 Extra Heavy Weight Fabric

⑤送具型式  
Feed Dog Type

2	2排 (標準) 2 Row (Standard)
3	3排 (標準) 3 Row (Standard)
4	4排 (標準) 4 Row (Standard)
6	1排 (特殊) 1 Row (Special)
7	2排 (特殊) 2 Row (Special)
8	3排 (特殊) 3 Row (Special)

## OVERLOCK DD SERVO MOTOR

**747L-514M-3-24 / ECA / DKL□□**

⑨DKL□□ 700L型直驅電控組  
Direct Drive Servo Motor for 700L  
請參閱P.46-47 Detail on Page.46-47

卓越性能 來自不斷的淬煉

Excellent performance comes from  
constant refinement



# 700L

超 高 速 安 全 包 縫 機

Ultra High Speed Safety Overlock Sewing Machine



700L



## 700L series

在 SiRUBA 包縫機技術的既有基礎上，大幅度提升性能

### 追求控線與送布的根本性能，實現完美的縫紉品質

過線系統全面優化，在每一個細節都考慮了線的張力狀態，實現了極佳的控線能力。送具、壓具與切布刀的綜合調校，優化送布性能。在面料的厚薄適用性，700L在規格上有更全面的應對，實現了令人滿意的車縫品質。

**In pursuit of the core performance of thread controlling and fabric feeding, it realizes perfect sewing quality.**

Threading system is fully optimized. As we fine-tuned every detail about the thread tension, it realizes a very good thread controlling. The feed dog, presser foot, and fabric trimmer are well coherent to make the fabric feeding optimized. Regarding the applicability range of fabric weight, 700L has a more comprehensive correspondence by specification, and realizes the satisfactory seam quality.

### 在機械精度的追求，達到高速運轉下的穩定性

提升零件的製造工藝，在精度、表面處理、內孔精加工和零件的輕量化設計，每一個細節都嚴謹的配合，實現了高速、穩定、低噪音與低振動的機械性能。

**In pursuit of mechanical precision, it realizes the stability under high speed operation.**

Improving the spare parts manufacturing process, the spare parts manufacturing process is improved. As the precision, surface treatment, micro-finish honing and parts light weight design are strictly coordinated in details, it realizes the high speed, stable, low noise and vibration mechanical performance.

### 車縫應用的範圍更寬

針對車縫面料的厚度，在規格上(包括規格組、上勾針行程、機構時位...等)有更全面的對應，超薄或超厚的面料都有令人滿意的車縫品質。

**The wider range of sewing application**

Regarding sewing material thickness, we have a full specification (including gauge set, upper looper stroke, mechanical timing... etc) to satisfy customer requirement. We provide the nice seam quality in sewing fine or extra heavy material.

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

# 747L - 514 M - 3 - 24 / VT

- ① 線數 Thread numbers
- ② 機種別 Model
- ③ 縫合方式 Sewing types
- ④ 車縫布料/上勾針縫容量 Sewing fabric/Upper looper capacity
- ⑤ 送具型式 Feed dog type
- ⑥ 針距 Needle gauge
- ⑦ 包邊寬度 Overedge width
- ⑧ 配件 Device
- ⑨ 馬達 Motor U : U Series / H : H Series

700L	布料厚度 Fabric Weight			①	⑥	⑦	⑧	⑨	! DCX27	S.P.M. (Max)
	L	M	H							

### 一般包縫 General Seaming

737L-503M-3-04		1	3	-	4	0.7~2	3.6	6	#11	7500
737L-504F-2-04		1	3	-	4	0.7~2	3.6	6	#11	7500
737L-504M-3-0⑦		1	3	-	4,5	0.7~2	3.6	6	#11	7500
747L-512M-3-25		2	4	2	5	0.7~2	3.6	5.5	#11	7500
747L-514M-3-2⑦		2	4	2	3,4,5	0.7~2	3.6	5.5	#11	7500
747L-514H-3-28		2	4	2	8	0.7~2	3.6	6.5	#11	6500
757L-516L-2-24		2	5	2	4	0.7~2	3.6	5.5	#14	7000
757L-516L-2-35		2	5	3	5	0.7~2	3.6	5.5	#14	7000
757L-516M-3-35		2	5	3	5	0.7~2	3.6	5.5	#14	7000
757L-516M-3-55		2	5	5	5	0.7~2	3.6	5.5	#14	7000
767L-644M-3-324		3	6	3+2	4	0.7~2	3.6	5.5	#11	7000
767L-644M-3-524		3	6	5+2	4	0.7~2	3.6	5.5	#11	7000

### 細包縫 Fine Edging

737L-504F-2-02/GAL		1	3	-	2	0.7~2	3.6	6	#9	7500
737L-504F-2-15		1	3	-	1.5	0.7~2	3.6	6	#9	7500
737L-504M-2-15		1	3	-	1.5	0.7~2	3.6	6	#9	7500

### 肩帶包縫 Tape Inserting

747L-514M-3-2⑦/TG		2	4	2	4,5	0.7~2	3.6	5.5	#11	7500
-------------------	--	---	---	---	-----	-------	-----	-----	-----	------

### 拷下擺 Blind Hemming

737L-505F-2-04		1	3	-	4	0.7~2	3.6	6	#9	7500
----------------	--	---	---	---	---	-------	-----	---	----	------

### 魚骨縫 Fishbone Stitch

747L-503M-2-23		1,2	2,3	-	3	0.7~2	-	5.5	#11	6500
----------------	--	-----	-----	---	---	-------	---	-----	-----	------

### 摺景車縫 Gathering

747L-514M-8-24/GA		2	4	2	4	0.7~2	3.6	5.5	#11	7000
757L-516M-8-35/GA		2	5	3	5	0.7~2	3.6	5.5	#14	7000
757L-516M-8-55/GA		2	5	5	5	0.7~2	3.6	5.5	#14	7000

規格索引，詳細請參考P.37 Specification index, please refer to P.37

700L	布料厚度 Fabric Weight				①	⑥	⑦				! DCX27	
	L	M	H									
<b>鬆緊帶車縫 Elastic Attaching</b>												
737L-504M-3-04/LFC-3				1	3	-	4	0.7~2	3.6	6	#11	4500
737L-WR/LFC-3				1	3	-	-	-	-	-	#11	4500
747L-514M-3-24/LFC-3				2	4	2	4	0.7~2	3.6	5.5	#11	4500
<b>手動線頭包縫 Manual Back Latching Seaming</b>												
737L-504M-7-04/BK				1	3	-	4	0.7~2	3.6	6	#11	7500
747L-514M-7-2/BK				2	4	2	3,4,5	0.7~2	3.6	5.5	#11	7500
747L-514H-7-25/BK				2	4	2	5	0.7~2	3.6	6.5	#16	6500
<b>全自動線頭包縫 Fully Auto Back Latching Seaming</b>												
737L-504M-3-04/BKF1				1	3	-	4	0.7~2	3.6	6	#11	6500
747L-514M-3-24/BKF1				2	4	2	4	0.7~2	3.6	5.5	#11	6500
<b>厚毛衣料包縫 Over Seaming On Bulky Knitwear</b>												
747L-514H-4-2				2	4	2	4,5	0.7~2	3.6	6.5	#16	6500
<b>牛仔安全縫 Jeans Safety Stitch</b>												
757L-516H-3-56				2	5	5	6	0.7~2	3.6	7	#16	6000
757L-516X-3-5 ※				2	5	5	5,6	0.7~2	3.6	7	#16	6000
<b>厚毛衣料肩帶包縫 Tape Inserting On Bulky Knitwear</b>												
747L-514H-4-24/TG/EC				2	4	2	4	0.7~2	3.6	6.5	#16	6500
747L-514H-4-25/TG/EC				2	4	2	5	0.7~2	3.6	6.5	#16	6500
<b>口袋邊包縫 Pocket Binding</b>												
757L-516M-3-35/PS				2	5	3	5	0.7~2	3.6	5.5	#14	7000
757L-516M-3-55/PS				2	5	5	5	0.7~2	3.6	5.5	#14	7000
757L-401M-8-0/TA				2	4	3,5	-	0.7~2	3.6	5.5	#14	7000
<b>氣動式切刀 Pneumatic Type Tape/Thread Cutter</b>												
737L-504M-3-04/ECA(-U)				1	3	-	4	0.7~2	3.6	6	#11	7000
747L-514M-3-24/ECA(-U)				2	4	2	4	0.7~2	3.6	5.5	#11	7000
747L-514M-3-24/ECA/BKT				2	4	2	4	0.7~2	3.6	5.5	#11	7000
747L-514H-3-28/ECA(-U)				2	4	2	8	0.7~2	3.6	6.5	#11	6500
747L-514H-4-25/ECA-U				2	4	2	5	0.7~2	3.6	6.5	#16	6500
757L-516M-3-5/ECA(-U)				2	5	3,5	5	0.7~2	3.6	5.5	#14	7000
757L-516H-3-55/ECA-U				2	5	5	5	0.7~2	3.6	7	#16	6500
757L-516X-3-56/ECA-U				2	5	5	6	0.7~2	3.6	7	#16	6000
767L-644M-3-324/ECA-U				3	6	3+2	4	0.7~2	3.6	5.5	#11	7000

※ 搭配厚料修布角刀  
With heavy material angle knife.

# 700L

布料厚度  
Fabric Weight

L	M	H
---	---	---



## 電動式切刀 Solenoid Type Tape/Thread Cutter

737L-504M-3-04/ECB(-U)		1	3	-	4	0.7~2	3.6	6	#11	7000
747L-514M-3-27/ECB(-U)		2	4	2	3,4	0.7~2	3.6	5.5	#11	7000
747L-514H-3-28/ECB		2	4	2	8	0.7~2	3.6	6.5	#11	6500
747L-514M-3-23/ECB-U		2	4	2	3	0.7~2	3.6	5.5	#11	7000
747L-514H-4-25/ECB-U		2	4	2	5	0.7~2	3.6	6.5	#16	6500
757L-516M-3-55/ECB(-U)		2	5	3,5	5	0.7~2	3.6	5.5	#14	7000
757L-516X-3-56/ECB-U		2	5	5	6	0.7~2	3.6	7	#16	6000
767L-644M-3-324/ECB(-U)		3	6	3+2	4	0.7~2	3.6	5.5	#11	7000
767L-644M-3-524/ECB-U		3	6	5+2	4	0.7~2	3.6	5.5	#11	7000

## 側吸式自動切線裝置 (附電眼節能裝置)

Side Suction Auto Thread Chain Cutter Device (with Sensor-Controlled Energy-Saving Device)

737L-504M-3-04/VTE(-U)		1	3	-	4	0.7~2	3.6	6	#11	7000
737L-504F-2-15/ VTE		1	3	-	1.5	0.7~2	3.6	6	#9	7000
747L-514M-3-24/ VTE(-U)		2	4	2	4	0.7~2	3.6	5.5	#11	7000
747L-514H-3-28/ VTE		2	4	2	8	0.7~2	3.6	6.5	#11	6500
747L-514M-3-24/ VTA		2	4	2	4	0.7~2	3.6	5.5	#11	7000

## 下吸式自動切線裝置 (附電眼節能裝置)

Flat Suction Auto Thread Chain Cutter Device(with Sensor-Controlled Energy-Saving Device)

747L-514M-3-24/ CTE(-U)		2	4	2	4	0.7~2	3.6	5.5	#11	7000
757L-516L-2-24/ CTE(-U)		2	5	2	4	0.7~2	3.6	5.5	#14	7000
757L-516M-3-35/ CTE(-U)		2	5	3	5	0.7~2	3.6	5.5	#14	7000
757L-516M-3-55/ CTE(-U)		2	5	5	5	0.7~2	3.6	5.5	#14	7000
757L-516X-3-56/ CTE(-U) ※		2	5	5	6	0.7~2	3.6	7	#16	6000

## 下吸式切線裝置 Flat Suction Thread Chain Cutter Device

767L-644M-3-324/CT		3	6	3+2	4	0.7~2	3.6	5.5	#11	7000
767L-644M-3-524/CT		3	6	5+2	4	0.7~2	3.6	5.5	#11	7000

## 電動式切布條 / 鬆緊帶條裝置 Electric Type Tape / Elastic Trimmer

747L-514M-3-24/ EC		2	4	2	4	0.7~2	3.6	5.5	#11	6500
--------------------	--	---	---	---	---	-------	-----	-----	-----	------

## 上下層防捲邊 Top and Bottom Anti-Curly Material

747L-514M-3-24/VT/UC		2	4	2	4	0.7~2	3.6	5.5	#11	7000
----------------------	--	---	---	---	---	-------	-----	-----	-----	------

※ 搭配厚料修布角刀  
With heavy material angle knife.

# 700L 直驅系列

## 700L DD Motor Series

承續 700QD 系列的豐富實戰經驗，SiRUBA 電控技術再提升  
Based on the rich experience of 700QD Series, SiRUBA upgrades the control technology.



### 採用高速伺服馬達

- 以充沛的動力，實現7500 RPM的運轉速度
- 製造精度高，噪音小，發熱低

### 採用新型電眼，更靈敏，更精準，偵測無死角

- 體積極小，安裝於車布板下方，單一方向偵測布邊
- 不需調整電眼位置，適用於各種車縫作業情形
- 克服因棉絮阻擋而造成感測失靈的問題

### 控制器模組化設計，以多種組合，全方位滿足各種需求

- 經濟型：節能省電，並可驅動EC切布條裝置
- 多功能型：標配電眼，偵測布料邊緣，以進行自動模式車縫，並可切換半自動或手動模式
- 多功能型分為氣動型與電動型，依客戶的廠房設備，選擇適合的規格

### The high speed servo motor

- By the plenty power, it realizes the operation speed of 7500 RPM.
- High precision makes low noise level and low heat.

### The new sensor is more sensitive, more accurate, no blind spot.

- It is very small, installed under the sewing bed, detecting the fabric by single direction.
- No need to adjust the position, apply to a variety of sewing operations.
- Overcoming the problem of sensory failure due to dust blocking.

### The controller modularized design, with a variety of combinations, comprehensively meets the various demands.

- Economic type: Energy saving, and also drives EC device, electrical tape trimmer.
- Multi-function type: the sensor checks fabric edge for automatic sewing mode. Also semi-auto or manual mode can be switched on demand.
- Multi-function type includes pneumatic and electrical type. Customers may choose the suitable specification according to the factory facility.

## 700L 產品組合：配件與直驅電控組

### Product Package: Devices and Direct Drive Control Sets

直驅電控組 Direct drive Control Set	配件 Device	功能 Function	配件表 Accessory List														
			電眼 Sensor	安全 開關 Safety Switch	操作 面板 Control Panel	手動 開關 Manual Cut Switch	鬆線 Thread Release	切布條 Tape Cutter	吸風切線 Suction Trimmer		LED 照明 LED Light	立式 踏板 Standing Operation Padel	抬壓腳 Auto Foot Lifter	吸風組 Suction Set	針板 Needle Plate		
									側切 Side Cutter	平切 Flat Cutter							
		一般車縫 General Sewing															
DKLH□-0 經濟型 Economic Type	VT	吸風切線 Suction Thread Chain Cutter								●		●			#4	#3 #4	標準型 Standard
	CT	吸風切線 Suction Thread Chain Cutter									●		●		#4	#3 #4	
	EC*	電動切布條 Electric Type Tape Trimmer				●			●			●					

\* 分標準切刀 EC-K (16 mm) · 長切刀 EC-K-A (22 mm)

\*EC-K: Standard knife (16 mm") EC-K-A: Long knife (22 mm")

直驅電控組 Direct drive Control Set	配件 Device	功能 Function	配件表 Accessory List												
			電眼 Sensor	安全 開關 Safety Switch	操作 面板 Control Panel	手動 開關 Manual Cut Switch	鬆線 Thread Release	切布條 Tape Cutter	吸風切線 Suction Trimmer		LED 照明 LED Light	立式 踏板 Standing Operation Padel	抬壓腳 Auto Foot Lifter	吸風組 Suction Set	針板 Needle Plate
									側切 Side Cutter	平切 Flat Cutter					
DKLH□-1 多功能 氣動型 Multi-function Pneumatic Type	ECA	氣動式切刀 Pneumatic Thread Cutter	●	●	●	●					●	#2	●	●	
	VTE	吸風切線 Suction Thread Chain Cutter	●	●	●		#1		●		●	#2	●	●	
	VTA	吸風切線 Suction Thread Chain Cutter	●	●	●		#1		●		●	#2	●	●	
	CTE	吸風切線 Suction Thread Chain Cutter	●	●	●		#1			●	●	#2	●	●	
	UC	上下層防捲邊 Top and Bottom Anti-Curly Edge		●	●				●		●	#2	●	●	標準型 Standard
	BKT	簡易型自動包線頭 Simplified Auto Back Latch	●	●	●	●		●			●	#2	●	●	
DKLH□-2 多功能電動型 Multi-function Electric Type	ECB	電動式切刀 Solenoid Thread Cutter	●	●	●	●					●	#2	● Solenoid Type	●	
DKLU□-0 經濟型 Economic Type		一般車縫 General Sewing									●				
DKLU□-1 多功能型 Multi-function Type	ECA-U	氣動式切刀 Pneumatic Thread Cutter	●	●	●	●					●	#2	●	●	
	ECB-U	電動式切刀 Solenoid Thread Cutter	●	●	●	●					●	#2	● Solenoid Type	●	加長型 Long type
	VTE-U	吸風切線 Suction Thread Chain Cutter	●	●	●	●	●		●		●	#2	●	●	
	CTE-U	吸風切線 Suction Thread Chain Cutter	●	●	●	●				●	●	#2	●	●	

備註 Remark :

● 標準配備 Standard accessory : 吸風組為 700L 電眼型之標準配備 The suction set is standard accessory of 700L sensor type models.

# 選配 Optional accessory :

#1: BK321-4 | #2: EC467-A | #3: ①TUA-31 需有空壓設備 ②TUD-2 無電刷馬達驅動 | #4: TUA-32K 需有空壓設備

#1: BK321-4 | #2: EC467-A | #3: ①TUA-31 Air compressor is required. ②TUD-2 Driven by Brushless motor. | #4: TUA-32K Air compressor is required.

## TUA-3X

### 三合一吸風集塵組 3-IN-1 SUCTION DEVICE

代號 Code	功能組件 Functional Section			搭配 配件 Collocated Device	適用機型 Applicable Model
	三吸組 3-In-1 Suction Set	氣動抬壓腳 Pneumatic Presser Foot Lifter	機械閥 Mechanical Type Air Switch		
TUA-31	V	V	單聯 Single way	VT CT	700L
TUA-32K			雙聯 Double ways		



① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

# 737L - 504 F - 2 - 0 4 / DKLU

- ① 線數  
Thread numbers
- ② 機種別  
Model
- ③ 縫合方式  
Sewing types
- ④ 車縫布料/上勾針縫容量  
Sewing fabric/Upper looper capacity
- ⑤ 送具型式  
Feed dog type
- ⑥ 針距  
Needle gauge
- ⑦ 包邊寬度  
Overedge width
- ⑧ 配件  
Device
- ⑨ 馬達 Motor U : U Series / H : H Series

L1										Remark
737L-503M-3-04/(⑨)	1	3	-	4	0.7~2	3.6	6	H / U	7500	A
737L-504F-2-04/(⑨)	1	3	-	4	0.7~2	3.6	6	H / U	7500	
737L-504M-3-07/(⑨)	1	3	-	4,5	0.7~2	3.6	6	H / U	7500	B
747L-512M-3-25/(⑨)	2	4	2	5	0.7~2	3.6	5.5	H / U	7500	D
747L-514M-3-27/(⑨)	2	4	2	3,4,5	0.7~2	3.6	5.5	H / U	7500	C
747L-514H-3-28/(⑨)	2	4	2	8	0.7~2	3.6	6.5	H / U	6500	
757L-516L-2-24/(⑨)	2	5	2	4	0.7~2	3.6	5.5	H / U	7000	
757L-516L-2-35/(⑨)	2	5	3	5	0.7~2	3.6	5.5	H / U	7000	
757L-516M-3-35/(⑨)	2	5	3	5	0.7~2	3.6	5.5	H / U	7000	
757L-516M-3-55/(⑨)	2	5	5	5	0.7~2	3.6	5.5	H / U	7000	
767L-644M-3-324/(⑨)	3	6	3+2	4	0.7~2	3.6	5.5	H / U	7000	E
767L-644M-3-524/(⑨)	3	6	5+2	4	0.7~2	3.6	5.5	H / U	7000	E

## 一般包縫

適用於特薄至中厚布料之包縫。

### Remark

- A : 上勾針為盲勾針
- B : 單排送具
- C : 適用於薄至中厚布料之包縫
- D : 用於薄至中厚布料之一般縫合 (假五線)
- E : 適用於薄至中厚布料之一般縫合 · 適合小量生產的打樣室或工作室選用 · 可由勾針及針之變換車縫出5種不同的縫合方式 (504,514,516, 401, 644)

## GENERAL SEAMING

For regular seaming on light to medium fabric.

- A: Upper looper is blind looper
- B: Single row feed dog
- C : For regular seaming on light to medium fabric.
- D : Mock 516 seaming  
For regular seaming on light to medium fabric.
- E : For regular seaming on light to medium fabric.  
Specially suitable for small production workshop, and fashion design studio. A variety of five different sewing types by changing number of needle and looper. (504, 514, 516, 401, 644).



504



514



512



516



644(401+514)

選購配件 OPTIONAL DEVICE

\*CT, \*VT, TUA

\*注 : VT僅可搭配737L & 747L ; CT僅可搭配757L & 767L

\* Remark : VT only for 737L & 747L / CT only for 757L & 767L

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

# 737L-504F-2-02/GAL/DKLU

- ① 線數 Thread numbers
- ② 機種別 Model
- ③ 縫合方式 Sewing types
- ④ 車縫布料/上勾針縫容量 Sewing fabric/Upper looper capacity
- ⑤ 送具型式 Feed dog type
- ⑥ 針距 Needle gauge
- ⑦ 包邊寬度 Overedge width
- ⑧ 配件 Device
- ⑨ 馬達 Motor U : U Series / H : H Series

<b>L2</b>										Remark
737L-504F-2-02/GAL/(⑨)	1	3	-	2	0.7~2	3.6	6	H / U	7500	A
737L-504F-2-15/(⑨)	1	3	-	1.5	0.7~2	3.6	6	H / U	7500	B
737L-504M-2-15/(⑨)	1	3	-	1.5	0.7~2	3.6	6	H / U	7500	C

## 細包縫

- A. 適用於特薄布料之捲邊細包縫 (荷葉邊) 例如: 手帕、禮服等。
- B. 適用於特薄布料之捲邊細包縫 (手帕邊包縫) 例如: 絲綢類布料之手帕、禮服等。
- C. 適用於薄至中厚布料之細包縫 (手帕邊包縫) 例如: 手帕、禮服等。




737L-504F-2-02/GAL



## FINE EDGING

- A. For fine edging on extra light knit fabric. The presser foot is with fine folding function. (falbala edging)  
Eg : Handkerchief & dress...etc.
- B. For fine edging on extra light knit fabric. The presser foot is with fine folding function. (handkerchief edging)  
Eg : Handkerchief & dress of silk fabric...etc.
- C. For fine edging on light to medium fabric. (handkerchief edging)  
Eg : Handkerchief & dress ...etc.



A



B



C

選購配件 OPTIONAL DEVICE

VT, TUA

## L3

747L-514M-3-27/TG/(⑨)	2	4	2	4,5	0.7~2	3.6	5.5	H / U	7500
-----------------------	---	---	---	-----	-------	-----	-----	-------	------



747L-514M-3-24/TG/EC



## 肩帶包縫

適用於針織衣服如T恤、毛衣等之肩部多車一條織帶，可防止衣服肩部變形。

## TAPE INSERTING

For sewing a woven tape onto the shoulder of knitwear such as T-shirt or sweater etc., to prevent abnormal stretching.

選購配件 OPTIONAL DEVICE

EC, LFA, LS

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨  
**737L - 504 F - 2 - 0 4 / DKLU**

- ① 線數  
Thread numbers
- ② 機種別  
Model
- ③ 縫合方式  
Sewing types
- ④ 車縫布料/上勾針縫容量  
Sewing fabric/Upper looper capacity
- ⑤ 送具型式  
Feed dog type
- ⑥ 針距  
Needle gauge
- ⑦ 包邊寬度  
Overedge width
- ⑧ 配件  
Device
- ⑨ 馬達 Motor U : U Series / H : H Series

L4										
737L-505F-2-04/(⑨)	1	3	-	4	0.7~2	3.6	6	H / U	7500	



### 拷下擺

用於特薄至薄布料之針織T恤、內衣等之下擺或袖口拷縫。

### BLIND HEMMING

For hemming sleeves and bottoms of T-shirts or underwear etc. Applicable for light to extra light fabric.

選購配件 OPTIONAL DEVICE
VT, TUA

L5										
747L-503M-2-23/(⑨)	1,2	2,3	-	3	0.7~2	-	5.5	H / U	6500	




### 魚骨縫

適用於不同厚度、彈性的布料。布料透過魚骨縫拷克縫製，可以容易的將布料攤平，並在布料上呈現整齊且均勻的魚骨縫線跡，同時增加縫製產品的美觀性與舒適性。

### FISHBONE STITCH

Suitable for fabrics of different thickness and elasticity. Sewing with fishbone stitch can easily flatten the fabric, so that the stitches can be neatly placed on the fabric, which is good looking and comfortable to wear at the same time.



#### 魚骨縫寬度：

魚骨縫拷克具有較好的操作性與調整性，可依據縫製包邊寬度需求，選用單左針車縫或單右針車縫。使用單左針車縫，其魚骨縫寬度為5mm；使用單右針車縫，其魚骨縫寬度為3mm。

#### Width of fishbone stitch：

Fishbone stitch has good operability and adjustability. You can choose single left needle sewing or single right needle sewing according to the sewing width requirement. The width of fishbone stitch is 5mm with single left needle; the width of fishbone stitch is 3mm with single right needle.



ASO-FPM100

#### 魚骨扒縫機：

使用ASO-FPM100讓布料更平整、效果更佳，改善人工扒布造成的線跡不均問題。

#### Fishbone-seam Peeling Machine：

ASO-FPM100 will improve uneven seam issues caused by operator. Make finished product even and have better quality.



#### 雙線跡車縫：

輕鬆更換二線、三線，達成不同線跡飾縫。

#### Two Types Stitches Sewing：

Easily convert two threads to three threads for different seams requirement.

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

# 747L-514 M -8-2 4/GA/ DKLU

- ① 線數  
Thread numbers
- ② 機種別  
Model
- ③ 縫合方式  
Sewing types
- ④ 車縫布料/上勾針縫容量  
Sewing fabric/Upper looper capacity
- ⑤ 送具型式  
Feed dog type
- ⑥ 針距  
Needle gauge
- ⑦ 包邊寬度  
Overedge width
- ⑧ 配件  
Device
- ⑨ 馬達 Motor U : U Series / H : H Series

<b>L6</b>	①	⑥	⑦	④	⑤	⑥	⑦	⑨	S.P.M. (Max)
747L-514M-8-24/GA/⑨	2	4	2	4	0.7~2	3.6	5.5	H / U	7000
757L-516M-8-35/GA/⑨	2	5	3	5	0.7~2	3.6	5.5	H / U	7000
757L-516M-8-55/GA/⑨	2	5	5	5	0.7~2	3.6	5.5	H / U	7000



757L-516M-8-35\_GA



GA

## 折景車縫

適用中厚布料下層布間歇或連續性不規則折景車縫，可加滾邊喇叭增加車縫品質如裙子，床單，窗簾等。

## GATHERING

Continuous or intermittent random gathering on lower ply of medium fabric, can be equipped with piping folder to increase sewing quality for shirt, bed sheets, curtains etc.

<b>L7</b>	①	⑥	⑦	④	⑤	⑥	⑦	⑨	S.P.M. (Max)
737L-504M-3-04/LFC-3/⑨	1	3	-	4	0.7~2	3.6	6	U	4500
747L-514M-3-24/LFC-3/⑨	2	4	2	4	0.7~2	3.6	5.5	U	4500
737L-WR/LFC-3	1	3	-	-	-	-	-	-	4500



747L-514M-3-24/LFC-3

## 鬆緊帶車縫

利用送帶裝置控制鬆緊帶之張力，適用於泳衣，內衣褲或運動服飾之鬆緊帶包縫。

**LFC-3**：機械式送帶，多樣的壓腳可供選擇

**SMK**：電子計數式送帶

**SMK1-A-01** 附定位器，適合簡易伺服或離合器馬達

**SMK1-A-02** 以中繼線連接伺服馬達

## ELASTIC ATTACHING

Tape feeding device controls the tension. Applicable to swimming wear, underwear, sports wear's elastic band attaching.

**LFC-3** : Mechanic type elastic tape feeding various presser foots for optional demand.

**SMK**: Electric metering type elastic tape feeding **SMK1-A-01** with synchronizer for simple servo motor or clutch motor.


**SMK1-A-02** Connected to servo motor by encoder cable.

壓具 Presser foot	P216	P217	P218	WP219
鬆緊帶尺寸 Elastic Size	2~13mm	2~20mm	2~30mm	2~35mm
備註 Remark	標配 Standard	選配 Optional		

選購配件 OPTIONAL DEVICE
EC, LFA, LS



737L-WR/LFC-3



LFC-3

### 管狀布條車縫

將針織布條拷邊車縫後再反條成管形，適用於各種泳裝，睡衣或韻律服等管狀肩帶。

注：標準喇叭之布條入布寬度22mm(7/8")成型之管狀布條直徑為5mm。

### SPAGHETTI SEWING

To sew knit fabric tape and turn over it into spaghetti tube for swimwears, nightgowns etc...

Remark : Standard folder specification: tape width is 22mm (7/8") and the finished tube size is about 5mm in diameter.

選購配件	OPTIONAL DEVICE
	FG

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

# 737L - 504 M - 7 - 0 4 / BK / DKLU

- ① 線數  
Thread numbers
- ② 機種別  
Model
- ③ 縫合方式  
Sewing types
- ④ 車縫布料/上勾針縫容量  
Sewing fabric/Upper looper capacity
- ⑤ 送具型式  
Feed dog type
- ⑥ 針距  
Needle gauge
- ⑦ 包邊寬度  
Overedge width
- ⑧ 配件  
Device
- ⑨ 馬達 Motor U : U Series / H : H Series

L8										
	1	3	6	7	mm	mm	mm	9	S.P.M. (Max)	
<b>手動 Manual</b>										
737L-504M-7-04/BK/(⑨)	1	3	-	4	0.7~2	3.6	6	H / U	7500	
747L-514M-7-2⑦/BK/(⑨)	2	4	2	3,4,5	0.7~2	3.6	5.5	H / U	7500	
747L-514H-7-2⑦/BK/(⑨)	2	4	2	5	0.7~2	3.6	6.5	H / U	6500	
<b>簡易式全自動 Simplified Fully Auto</b>										
747L-514M-3-24/ECA/BKT/⑨	1	3	-	4	0.7~2	3.6	7	H	7000	
<b>全自動 Fully Auto</b>										
737L-504M-3-04/BKF1/⑨	1	3	-	4	0.7~2	3.6	6	S	6500	
747L-514M-3-24/BKF1/⑨	2	4	2	4	0.7~2	3.6	5.5	S	6500	



747L-514M-7-24/BK



747L-514M-3-24/ECA/BKT



747L-514M-3-24/BKF1




## 線頭包縫

將線頭包入車縫線內，可防止縫合之開口處縫線脫落，適用於內衣褲，運動服之袖口及側邊縫合。

## BACK LATCHING SEAMING

To prevent seam looseness, turn over the thread and then insert into overlock seaming at the beginning of sewing. For sleeve and sideways sewing of underwear, sportswear etc.

操作 Operation	配件代號 Code	說明 Description	適用機頭 Applicable Series	驅動方式 Drive Type
手動 Manual	BK	Rotary Plate 	737L 747L	建議搭配伺服馬達， 使用定針功能， 提升車縫效率 To equip with servo motor for needle position function is optional and recommended.
簡易式全自動 Simplified Fully Auto	BKT	1. 簡易式，線頭長度約3cm 2. ECA切刀，針板有特殊風道設計，線頭向下吸回 1. Simplified type, back latch length 3cm. 2. With ECA cutter, needle plate suction channel for thread-end down turning.	747L	700L電控系統 氣動式 700L : Pneumatic type servo control system
自動 Fully Auto	BKF1	1. VT吸風切線 2. 可設定多種操作模式 3. 線頭側向吹回，長度可以調整 (最短2.5cm) 1. With VT suction trimmer 2. Multi-operation mode setting 3. Thread-end side turning. Back latch length is adjustable (Min. 2.5cm)	737L 747L	BKF1專用伺服控制系統 氣動式 BKF1 : Pneumatic type servo control system

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

# 737L - 514 H - 4 - 2 4 / DKLU

- ① 線數  
Thread numbers
- ② 機種別  
Model
- ③ 縫合方式  
Sewing types
- ④ 車縫布料/上勾針縫容量  
Sewing fabric/Upper looper capacity
- ⑤ 送具型式  
Feed dog type
- ⑥ 針距  
Needle gauge
- ⑦ 包邊寬度  
Overedge width
- ⑧ 配件  
Device
- ⑨ 馬達 Motor U : U Series / H : H Series

L9									
747L-514H-4-2⑦ / (③)(⑨)	2	4	2	4,5	0.7~2	3.6	6.5	H / U	6500
747L-514H-4-2⑦/TG/EC/(⑨)	2	4	2	4,5	0.7~2	3.6	6.5	H / U	6500
757L-516H-3-56	2	5	5	6	0.7~2	3.6	7	H / U	6000
757L-516X-3-5⑦	2	5	5	5,6	0.7~2	3.6	7	H / U	6000



747L-514H-4-24/TG/EC

757L-516X-3-56



### 厚毛衣料肩帶包縫

適用於毛衣之肩部多包縫一條平織布條，可防止衣服肩部變形。  
注：布條裝置之導板使用，布條最大寬度為1/4"(6.35mm)。

### TAPE INSERTING ON BULKY KNITWEAR

For sewing a woven tape onto the shoulder of knitwear such as sweater, to prevent abnormal stretching.  
Remark : Max. width of tape is 1/4"(6.35mm)

TG/EC

TG/EC 選購配件 OPTIONAL DEVICE

LFA, LS



### 厚毛衣料包縫

適用於粗厚毛線衣物車縫。

### OVER SEAMING ON BULKY KNITWEAR

For regular seaming on bulky knit fabric such as sweater.

514H4

514H4 選購配件 OPTIONAL DEVICE

CT, TUA



### 牛仔包縫

特殊傳動行程結構適用於牛仔布料之包縫，例如：牛仔布 & 工作服。

### DENIM OVERLOCK

Special driving mechanism for seaming on denim fabric such as jeans, workwears etc.

516X-3



516X3 選購配件 OPTIONAL DEVICE

CT, TUA

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

# 757L-516 M -3- 3 5/ PS / DKLU

- ① 線數  
Thread numbers
- ② 機種別  
Model
- ③ 縫合方式  
Sewing types
- ④ 車縫布料/上勾針縫容量  
Sewing fabric/Upper looper capacity
- ⑤ 送具型式  
Feed dog type
- ⑥ 針距  
Needle gauge
- ⑦ 包邊寬度  
Overedge width
- ⑧ 配件  
Device
- ⑨ 馬達 Motor U : U Series / H : H Series

<b>L10</b>										
757L-516M-3-35/PS/(⑨)	2	5	3	5	0.7~2	3.6	5.5	H / U	7000	
757L-516M-3-55/PS/(⑨)	2	5	5	5	0.7~2	3.6	5.5	H / U	7000	
757L-401M-8-⑥0/TA/(⑨)	2	4	3,5	-	0.7~2	3.6	5.5	H / U	7000	



757L-516M-3-35/PS



757L-401M-8-50/TA



PS



TA

## 口袋邊包縫

**PS :** 在褲袋邊緣縫包邊布條，以強化縫合處，增加美觀。

注：標準喇叭之入布寬度為3/8”(9.5mm)。

**TA :** 雙勾針機型，適用於褲袋邊緣加包邊布條，車縫兩道環縫線以強化縫合處並增加美觀。

注：標準喇叭(入布寬度25.4mm/出布寬度6.4mm)。



## POCKET BINDING

**PS :** To insert an extra tape to cover on the edge of pocket then by safety stitching for strengthening the pocket seaming. Suitable for high quality trousers.

Remark : Standard folder for tape width is 3/8”(9.5mm)

**TA :** Two needle two chainstitches. Tape binding by two chainstitch on the edge of pocket of high quality trousers.

Remark : Standard folder (tap width 25.4mm/finish width 6.4mm)

選購配件 OPTIONAL DEVICE







EC\* . FG

\*注：EC僅可搭配PS

\* Remark : EC only for PS

# OVERLOCK SEWING MACHINE

**747 KST - 514 M - 3 - 2 4 / VT**

<p>①線數 Thread Numbers</p> <p>737 : 3T 747 : 4T 757 : 5T</p>		<p>⑥針距 Needle Gauge</p> 	<p>⑦包邊寬度 Overedge Width</p> 	<p>⑧配件 Device</p>
<p>②機種別 Model</p> <p>KST 筒型上送 Cylinder-Bed Top-Feed</p> <p>KS 筒型 Cylinder-Bed</p> <p>KT 上送型/安全縫 Top-Feed/Safety Stitch</p>	<p>③縫合方式 Sewing Types</p> <p>504 </p> <p>505 </p> <p>514 </p> <p>516 *For KT </p>	<p>④車縫布料/上勾針縫容量 Sewing Fabric/Upper Looper Capacity</p> <p>F 輕薄布料 Fine Weight Fabric</p> <p>M 中厚布料 Medium Weight Fabric</p> <p>H 厚布料 Heavy Weight Fabric</p> <p>X 特厚布料 *For KT Extra Heavy Weight Fabric</p> 	<p>⑤送具型式 Feed Dog Type</p> <p>2 2排 (標準) 2 Row (Standard)</p> <p>3 3排 (標準) 3 Row (Standard)</p> <p>4 4排 (標準) 4 Row (Standard) *For KT</p>	

## OVERLOCK DD SERVO MOTOR

**747KST-514M-3-24 / VT / DKK□□**

⑨DKK□□ 700KST/700KS/700KT型直驅電控組  
Direct Drive Servo Motor for 700KST/  
700KS/700KT  
請參閱P.63 Detail on Page.63

# 700KS/KST series FEATURES

## 700KS 高速筒型包縫機 High Speed Cylinder Bed Overlock Sewing Machine

## 700KST 高速筒型上送包縫機 High Speed Cylinder Bed Top Feed Overlock Sewing Machine

延續700K系列之特點，發展筒型機構延伸成為700KS系列。再增加新型獨立驅動的上送具機構，延伸成為700KST系列

Succeeding 700K Series' features, we develop cylinder bed mechanism to extend to 700KS Series. Moreover, with brand new independent-drive top feed mechanism, it extends to 700KST Series.

- 筒嘴周長: 148mm · Cylinder Bed Circumference: 148mm
- 縫距調整: 按鈕式 · Stitch Length Adjustment: Push-button
- 差動比調整: 手杆式 · Differential Feed Ratio Adjustment: Lever type
- 潤滑系統: 全自動 · Lubrication: Fully-automatic



700KS											選購配件 OPTIONAL DEVICE
下擺盲縫 Blindstitch Hemming											
737KS-505F-2-04/⑨	1	3	-	4	0.7~2	3.8	5	#9	6500		
一般包縫 General Sewing											
737KS-504M-3-0⑦/⑧/⑨	1	3	-	3,4,5	0.7~2	3.8	5	#11	6500	VT	RLK- □
737KS-504H-3-0⑦/⑧/⑨	1	3	-	3,4,5	0.7~2	3.8	6	#11	6300	LFD6-K1	LFD6A-K1
747KS-514M-3-2⑦/⑧/⑨	2	4	2	3,4,5	0.7~2	3.8	5	#11	6500		
747KS-514H-3-2⑦/⑧/⑨	2	4	2	3,4,5	0.7~2	3.8	6	#11	6300		
700KST											選購配件 OPTIONAL DEVICE
下擺盲縫 Blindstitch Hemming											
737KST-505F-2-04/⑨	1	3	-	4	0.7~2	0.5~6	3.8	5	#9	6300	
一般包縫 General Sewing											
737KST-504M-3-0⑦/⑧/⑨	1	3	-	3,4,5	0.7~2	0.5~6	3.8	5	#11	6300	VT
737KST-504H-3-0⑦/⑧/⑨	1	3	-	3,4,5	0.7~2	0.5~8	3.8	6	#11	6000	RLK- □
747KST-514M-3-2⑦/⑧/⑨	2	4	2	3,4,5	0.7~2	0.5~6	3.8	5	#11	6300	
747KST-514H-3-2⑦/⑧/⑨	2	4	2	3,4,5	0.7~2	0.5~8	3.8	6	#11	6000	

專用選購配件

EXCLUSIVE OPTIONAL DEVICE

上圓領系列

CIRCULAR COLLAR ATTACHING SERIES



ACS


自動上圓領裝置

Automatic Circular Collar Attaching Device

在氣動導布與滾輪撐開的基礎上，加上自動順布條，接縫骨自動定位，減少90%的上料時間。

Based on Pneumatic tape guide and tubular extending roller set, with advanced function as Automatic tape alignment, automatic Joint-seam positioning, which reduce 90% material loading time.

- 1 自動偵測縫骨位置，減少工人對位時間。  
Auto detect the collar seam, by sensor. shorten the rib marking time.
- 2 可調式張力控制機構，減少布料起皺現象。  
Tubular tension control system avoids puckering.
- 3 導布結構，縫合衣領與布身時，防止偏斜。  
Guiding platform ensures a quality joint of rib and fabrics.
- 4 電眼控制導布裝置自動開合。  
Automatically control the fabric guider.



型號 Model	ACS200	領圍車縫範圍 Applicable Collar Circumference	
搭配縫紉機機頭 Machine Head	747KST-514M-3-24/VT		
車縫速度 Sewing Speed	4500 SPM (最高 Max)	領高車縫範圍 Applicable Collar Height	Single Phase 1Φ AC200~240V 50/60Hz
使用布料 Type of Fabric	彈性布料 Elastic fabric		
布厚車縫範圍 Applicable Cloth Thickness	對折後 1.2 mm ±0.2 mm After fold 1.2 mm ±0.2 mm	電源電壓 Power Supply	650 W (Max)
氣體消耗量 Air Consumption	150 公升 / 分 150 L/min	電力消耗 Power Consumption	
氣壓 Air Pressure	0.5 MPa	生產效率 Production Capacity	





**LFD6-K1 多功型自動鬆緊帶包縫(700KS 適用)**  
**LFD6A-K1 Multi-function computerized automatic elastic attaching**  
**(700KS Applicable)**



對於鬆緊帶之包縫，可利用電腦控制自動切帶與自動送帶。可設定多段之鬆緊度與車縫長度，適用於泳衣、緊身衣、內褲等小口徑鬆緊帶上帶車縫。

For attaching elastic tape on small openings of swimsuit, leotards or brief, etc. By computer control, with auto cutting and auto tape feeding, elastic tape sewing can be done by multi-section tension and length.



送具下沉功能：  
壓腳抬起時，送具自動下沉，確保送帶零干擾。

Feed dog dropping function : when presser foot lifts, the feed dog drops to ensure tape feeding without obstacle.



直驅伺服馬達：  
電控功能高度整合，動作配合更精確。

Direct drive servo motor : Electrics highly integration realizes the accurate series movements.

**LFD6-K1 & LFD6A-K1 規格/SPECIFICATION**



連續縫記憶組數 Program set memory	10組 10 sets
每組連續縫工程段數 Sections of every program	18段 18 sections
送帶距離/每針 Tape feeding length per stitch	0.2mm ~ 6.5mm
最高縫速(送距5mm) Max. Speed (stitch length 5mm)	4200 R.P.M
送帶馬達 Tape feeding motor	五相步進馬達 5-phase stepping motor
工作電壓 Voltage	AC 110~220 V

**送帶 / 切帶功能**

- 自動、手動、測試，三種操作模式。自動 / 手動換段，配備 LED 段數燈號
- 送帶精準，以 mm 為單位設定送帶長度
- 可調式前送帶，延遲送帶，倒帶功能，前送帶時可追加倒帶之功能
- 送帶速度補償，10 組預設值可供選擇
- 因應實際車縫狀況，車縫中可手動強制送帶 / 倒帶。車縫中遇失敗，可自動 / 手動調整至原工程第一段
- 吹氣送帶功能

**TAPE FEEDING / CUTTING**

- 3 operation modes: Auto, Manual, and Test. Auto/ Manual section changing with LED indicate lamp.
- Precise feeding and the length setting unit is mm.
- Adjustable feeding of forward, delay, reverse, and forward feeding with reverse function.
- Speed compensation with 10 default values for choice.
- For different sewing situations, active feeding may be applied by forward/ reverse when sewing. If sewing operation failed, auto/ manual return to the first section of sewing program.
- Air blow tape feeding function.

**設定 / 記憶功能**

- 連續縫記憶組數：10 組
- 工程段數：18 段
- LCD 面板顯示設定狀況、操作模式、錯誤代碼
- 觸控面板：圖形介面，設定更容易，添加測試模式，更快上手



**SETTING / MEMORY**

- Memory of sewing program set: 10 sets
- Program section: 18 sections.
- LCD panel shows setting status, operation mode, and error code.
- Touch panel : Graphical user interface is easy for setting. New added testing mode is easy for beginner.


**其他附屬功能**

- 鬆線功能
- 吸風切線之省風節能：起始 / 結束吸風時間可以調整 (以針數計算)
- 回踩自動抬壓腳功能


**Additional Function**

- Thread releasing
- Suction thread chain cutters energy saving: Starting/ Ending air suction's time is adjustable. (by stitch counting)
- Auto presser foot lifting by paddle step-back.

## 選配 / DEVICE



LFD6-A



LFD6-AA

Code	Description	Remark
LFD6-A	短滾輪：適用16mm以下之鬆緊帶 Short roller: for tape width 16 mm below	LFD6-K1 標配 LFD6-K1 Standard
LFD6-AA	長滾輪：適用16mm~50mm之鬆緊帶 Long roller: for tape width range 16mm~50mm	LFD6A-K1 標配 LFD6A-K1 Standard
LFA	電動式上送帶裝置 Electric tape feeding device Voltage, 110V(Part NO.LFA-1A) / 220V(Part NO.LFA-2A)	選配 Optional
LF290	抖帶輪 Euntangling wheel Voltage, 110V(Part NO.LF290-A1) / 220V(Part NO.LF290-A2)	選配 Optional
VT*	垂直式自動吸風切線 Vertical Pneumatic chain cutter	標配 Standard
TU*	空氣控制閥/集塵裝置 Dust collector suction device	標配 Standard



LF290

LFA

\* 標準配備不列入機型名稱  
\*Standard devices are not mentioned in model name.



### RLK1

筒型撐開輪組

Tubular Extending Roller set

- 前後撐開，搭配一般桌板
- Diagonal extending roller with closed table top



### RLK2

筒型撐開輪組

Tubular Extending Roller set

- 前後撐開，搭配開口式桌板
- Diagonal extending roller with open table top



### RLK3

筒型撐開輪組

Tubular Extending Roller set

- 三點式撐開，搭配開口式桌板
- Three point extending roller with open table top



### RLK3P

筒型撐開輪組(氣動)

Tubular Extending Roller set (pneumatic)

- 三點式撐開，搭配開口式桌板
- Three point extending roller with open table top
- 建議組合 Recommend Package TUA-38S(ST) / DKH201ADE-A / 700KS-T3-P



### RSK

圓領及褲頭車縫裝置

Circular collar & Waistband attaching device

1. 氣動式導布裝置，左右兩側緊靠圓領布帶，配合滾輪撐開組，使得圓領布帶能夠穩定的前進，車工只需控制布身裁片，提升效率，降低車縫工序的難度。
2. 分布裝置透過撥桿感測裝置，可控制布料避免移動走位。
3. 搭配賀欣直驅節能馬達、吸風集塵組(TUA-41ST)  
\*適用圓領、褲頭車縫。

1. Pneumatic fabric guide set holds the neckband's right and left side. With tubular extending roller set, the neckband tape can move forward stably so that operators can focus on fabric control, which improves the efficiency and reduces the difficulty of sewing operation.
2. The alignment device makes fabric edge aligned, shift-free during sewing.
3. Equipped with Hohsing direct drive energy saving motor & Dust Collecting Suction Device(TUA-41ST)  
\*For circular collar & waistband sewing.



# 700KT SERIES FEATURES



## 700KT 高速上送包縫機 High Speed Top Feed Overlock Sewing Machine

延續700K系列之特點，增加新型獨立驅動的上送具機構，  
延伸成為700KT系列。

- 縫距調整: 按鈕式
- 差動比調整: 手杆式
- 潤滑系統: 全自動

Succeeding 700K Series' features, we develop brand  
new independent-drive top feed mechanism, to extend  
to 700KT Series.

- Stitch Length Adjustment: Push-button
- Differential Feed Ratio Adjustment: Lever type
- Lubrication: Fully-automatic

### ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ 737KT - 504 M - 3 - 0 4 / VT / DKKU

- ① 線數 Thread numbers
- ② 機種別 Model
- ③ 縫合方式 Sewing types
- ④ 車縫布料/上勾針縫容量 Sewing fabric/Upper looper capacity
- ⑤ 送具型式 Feed dog type
- ⑥ 針距 Needle gauge
- ⑦ 包邊寬度 Overedge width
- ⑧ 配件 Device
- ⑨ 馬達 Motor U : U Series / H : H Series

#### 700KT



選購配件  
OPTIONAL  
DEVICE

#### 一般包縫 General Sewing

737KT-504M-3-0⑦/⑧/⑨	1	3	-	4,5	0.7~2	1~6	3.2	5	#9	6500	VT
747KT-514M-3-2⑦/⑧/⑨	2	4	2	3,4,5	0.7~2	1~6	3.2	5	#11	6500	VT
747KT-514H-4-2⑦/⑧/⑨	2	4	2	3,4,5	0.7~2	1~8	3.2	6	#11	6300	

#### 折景車縫 Shirring/Gathering

747KT-514H-3-2⑦/⑧/⑨	2	4	2	3,4,5	0.7~2	1~8	3.2	6	#11	6300	VT,GA
---------------------	---	---	---	-------	-------	-----	-----	---	-----	------	-------

#### 一般包縫 General Sewing

757KT-516M-3-3⑦/⑧/⑨	2	5	3	4,5	0.7~2	1~6	3.2	6	#14	6500	CT
757KT-516M-3-5⑦/⑧/⑨	2	5	5	5,6	0.7~2	1~6	3.2	6	#14	6500	CT
757KT-516H-3-5⑦/⑧/⑨	2	5	5	5,6	0.7~2	1~7	3.2	7	#21	6300	CT

#### 特厚布 Extra Heavy

757KT-516X-3-5⑦/⑧/⑨※	2	5	5	6,7	0.7~2	1~7	3.2	8	#21	5500	CT
----------------------	---	---	---	-----	-------	-----	-----	---	-----	------	----

※ 搭配厚料修布角刀  
With heavy material angle knife.

# DEVICE



**BK**


## 包線頭裝置 Back Latching

將線頭一起包入車縫，可防止縫合開口處(如袖口)之縫線脫落。

- KD207手輪: 訂機頭有裝此零件以配合定針用，若個別訂購BK組則依需要訂購
- 包含BK232車布導板

To prevent seam looseness, turn over the thread and then insert into overlock seaming at the beginning of sewing.

- KD207 hand wheel: standard equipment of 700K/BK machine, optional for BK device.
- Including BK232 sewing bed.



可自行組裝 self-installation : YES

適用機型 applicable model : 737L-504M-7, 747L-514M-7, 747L-514H-7



**BKT**

## 簡易式自動包線頭 Simply Auto Back Latch

為ECA延伸功能，車縫效率極高，針板有特殊風道設計，線頭在切線後，瞬間吸回，線頭長度約3cm。

It is an ECA extending function, the sewing efficiency is extremely high. The needle plate is specially designed with a suction channel to quickly retract the thread after trimming. The thread length is approximately 3cm.



可自行組裝 self-installation : NO

適用機型 applicable model : 747L-514M-3-24/ECA/BKT



**CT**

## 下吸式切線裝置 Flat Suction Thread Chain Cutter Device

利用吸風式馬達或空壓機，將線吸入切刀槽中予以切斷(較適用於4~6線之機型)。

Take thread into trimmer tube by suction motor or air compressor.  
(Applicable for 4~6 thread machine)

可自行組裝 self-installation : YES

適用機型 applicable model : 757L, 767L, 757KT



## CTE CTE-U

### 下吸式自動切線裝置 (附電眼節能裝置) Flat Suction Auto Thread Chain Cutter Device(with Sensor-controlled Energy-saving Device)

以電眼偵測布邊，控制吸風功能在切線時運作，減少空壓設備的能源消耗，並避免縫線浪費。

1. 垂直式吸風切線適合內褲等輕薄及不規則的針織面料車縫，提升效率。
2. 切刀之吸風口的設計使得切線更加快速。
3. 針對網紗、強反光絲光棉等特殊面料，採用專業的電控程式控制，均能輕鬆車縫及完成切線，不會造成切刀誤切。
4. 「切線後自動停車功能」以及「無面料即不車縫功能」可減少縫線的浪費。
5. VTA以氣缸推動切刀，減少刀刃磨耗，大幅延長使用壽命。

Sensor checks the fabric edge. It saves the energy consuming of air compressor system and also saves thread consuming.

1. Vertical suction trimming is suitable for sewing the light fabric like under-wear or irregular knitwear, to improve the efficiency.
2. The design of the suction inlet of the trimmer makes the trimming faster.
3. For those special fabrics such as mesh fabric, mercerized cotton etc, the stitches are easily accomplished as well as the trimming by the professional computer controlled without mistake-trimming.
4. Functions with auto stop sewing after trimming and with no fabric can save the stitches.
5. VTA trimmer is controlled by air cylinder, which reduces the blade stroke times and extends the durability.

	前/中電眼 Front/middle sensors	抬壓腳 Foot Lifter	氣動配件Pneumatic Set	
			吸風集塵組 Suction Set	吸風線槽 Suction Channel
CTE	V	氣動 Pneumatic	V	V
CTE-U	V	氣動 Pneumatic	V	V

可自行組裝 self-installation : NO

適用機型 applicable model : 757L



## DKL 12 DKK 12

### 直驅伺服馬達 Direct drive Servo Motor

包縫機模組化搭配直驅伺服馬達，多樣化的選擇，更有彈性。

1=廠商代碼 2=版本代碼 + 功能代碼

Overlock sewing machine equipped with the modularized direct drive servo motors to be more flexible for diversification.

1=Manufacturer code 2=Version code + Function code

可自行組裝 self-installation : YES

適用機型 applicable model : 全系列包縫機 All Overlock Series



## EC

### 電動式切布條/鬆緊帶條裝置 Electric Type Tape / Elastic Cutter

利用手動按鈕方式切斷鬆緊帶，不織布條或滾邊布條。

1. 分標準切刀ECL1-A (16 mm) · 長切刀EC-L1-A (22 mm)。
2. 標準為手動切帶，另可選購膝控切帶(FEC34-A)

Cuts tape/ elastic by pressing the button.

1. ECL1-A: Standard knife (16 mm") EC-L1-A: Long knife (22 mm")
2. Hand-control button : standard Knee-control paddle (FEC34-A) : Optional



可自行組裝 self-installation : YES

適用機型 applicable model : MODEL w/LFC-3, MDDEL w/PS, MODEL w/TG



**ECA**  
**ECB**

**氣動式切刀 (自動模式切換功能/附手動)**  
**Pneumatic Type Tape / Thread Cutter ( with Auto / Manual Switch Function)**

**電動式切刀 (自動模式切換功能/附手動)**  
**Solenoid Type Tape / Thread Cutter ( with Auto / Manual Switch Function )**

採用新一代的電眼，性能再升級。ECA為氣動式，ECB為電動式，搭配吸風線槽，操作更順暢。

1. 手動、半自動及全自動操作模式，附轉換按鍵，且可透過操作面板調整。
2. 防誤切保護裝置:切刀旁安裝一電眼，如有被遮擋的狀況下，切刀不會動作，能有效地防止切刀誤切到布料。
3. 手動切線補償按鍵，如因操作問題沒有切斷線，可由此按鍵進行手動切線。
4. 手動模式下，可後踩踏板切線。
5. 針對網紗、強反光絲光棉等特殊面料，採用專業的電控程式控制，均能輕鬆車縫及完成切線，不會造成切刀誤切。



Brand new sensor upgrades the performance. ECA is pneumatic type, and ECB is electric type, compatible with air suction slot, which makes the operation more smoothly.

1. Manual, semi-auto and fully-auto operation mode, attached the switch keys, and could be adjusted by the panel.
2. Mistake-proof protection device: One sensor equipped near the trimmer. If the sensor is blocked, the trimmer is deactivated effectively for avoiding from cutting the fabric.
3. Manual trimming compensation stitch key: If the thread is not cut due to the operation, it can be done by the key.
4. Under the manual mode, it could be fully backward pedaled to cut the thread.
5. For those special fabrics such as mesh fabric, mercerized cotton etc, the stitches are easily accomplished as well as the trimming by the professional computer controlled without mistake-trimming.

	三電眼 Three sensors	切刀 Cutter	抬壓腳 Foot Lifter	氣動配件Pneumatic Set	
				吸風集塵組 Suction Set	吸風線槽 Suction Channel
ECA / ECA-U	√	氣動 Pneumatic	氣動 Pneumatic	√	√
ECB / ECB-U	√	電動 Electric	電動 Electric	√	√

可自行組裝 self-installation : NO

適用機型 applicable model : 737L, 747L 757L, 767L



**FG**

**側帶盤 Side Tape Holder**

置於桌板右側放布條用。

For tape feeding, on the right side of the table.

可自行組裝 self-installation : YES

適用機型 applicable model : MODEL w/PS, MODEL w/TA



**GA**

**折景裝置 Gathering Device**

下層布間歇或連續性不規則折景。

P滾邊器(喇叭)KV57(入布寬度25mm/出布寬度6mm)依需要可另訂，若滾邊加繩需另訂壓具(壓具底需磨一條溝)，為一般壓具代號多加P，如：P204P。

Continuous or intermittent random gathering on lower ply.

P: Piping folder KV57 (tape width 25mm / finish width 6mm) is optional. For piping with rope inside, presser foot requires a trench, which is marked with P at the end of parts code. eg P204P.

可自行組裝 self-installation : YES

適用機型 applicable model : 747KT-514H, 747L-514M-8, 757L-516M-8



## GAS 折景壓腳 Gathering Presser-foot

下層布間歇或連續性不規則折景。料號：ZGL04-P324-A。  
Continuous or intermittent random gathering on lower layer of fabric.  
Part NO. ZGL04-P324-A

可自行組裝 self-installation : YES  
適用機型 applicable model : 747L-514M



## GAL 荷葉邊密拷裝置 Flounce/Falbala fine edging

彈性布料密合時，以壓布杆向下壓住布料邊緣，形成向後拉力，而產生荷葉邊造型，可調整壓力產生不同的波浪效果。  
Elastic fabric fine serging with a pull-back device makes flounce/ falbala style.  
Adjust the pressure of pull-back plate to have big or small waves.


可自行組裝 self-installation : YES  
適用機型 applicable model : 737L-504F-2



## KB301 簡易防捲邊裝置 Simple anti curly selvedge device

安裝容易，透過裝置有效輔助捲曲布料工段之車縫。  
Easy to install, effectively solve curly selvedge problem.

可自行組裝 self-installation : YES  
適用機型 applicable model : MODEL 700L, MODEL 700KT



## KB561-A 平台式車布導板 Flat Bed Cloth Plate

將筒型車改為平台式，方便於非筒型衣物包縫。  
To convert cylinder bed machine into flat bed machine. For normal overlock sewing operation.

可自行組裝 self-installation : YES  
適用機型 applicable model : 700KS



## FA 側向電動送帶裝置 Side Electric Tape Feeding

1. 利用電子微動開關控制布條，鬆緊帶或蕾絲之輸送長度，使上帶車縫更加平順。
2. 送帶在控制箱右邊。
1. With electronic switch to control the feeding length of tape, elastic, or lace to create smoother sewing.
2. Tape feeding will be on the right hand side of the control box.

可自行組裝 self-installation : YES  
適用機型 applicable model : 700L



## LFA

### 電動式直向送帶裝置 Electric Type Upper Tape Feeding Device

利用電子馬達帶動鬆緊帶，使其放鬆到零鬆緊狀況，並可控制所需鬆緊帶之長短，使車縫時鬆緊度能一致。

電壓：110V(Part NO. LFA-1A) / 220V(Part NO. LFA-2A)

To keep constant tension for sewing. Elastic tape is fed by motor for zero tension and required length.

Voltage, 110V(Part NO. LFA-1A) / 220V(Part NO. LFA-2A)

可自行組裝 self-installation : YES

適用機型 applicable model : MODEL w/LFC-3, MODEL w/TG



## LF290

### 抖帶輪 Untangle Wheel

可選配安裝於LFA (送帶裝置)，以逆轉的方式，抖動鬆緊帶，做為送帶前的處理。

電壓：110V(Part NO. LF290-A1) / 220V(Part NO. LF290-A2)

An optional device to be equipped with LFA (tape feeding device). Untangling the elastic tape by reverse rotation wheel is a pre-feeding process.

Voltage, 110V(Part NO. LF290-A1) / 220V(Part NO. LF290-A2)

可自行組裝 self-installation : YES

適用機型 applicable model : MODEL w/LFA



## LFC-3

### 機械式鬆緊帶送帶裝置 Mechanical Type Elastic Feeding

利用齒輪調整控制鬆緊帶之鬆緊程度；壓具:分3線及4線用如：P216-3，P216-4 (標準品配P216除非下單時註明)。

To Control elastic tape tension by adjusting the gear.

Presser foot:

P216-3 for 3 thread

P216-4 for 4 thread

Standard is P216. Special demand by request.

壓具 Presser foot	P216	P217	P218	WP219
鬆緊帶尺寸 Elastic Size	2~13mm	2~20mm	2~30mm	2~35mm
備註 Remark	標配 Standard	選配 Optional		

可自行組裝 self-installation : YES



## LS

### 上方帶盤 Upper Tape Holder

置於上前方放布條或鬆緊帶。

For top feeding tape or elastic.

可自行組裝 self-installation : YES

適用機型 applicable model : MODEL w/LFC-3, MODEL w/TG



## PS

### 口袋包邊縫合裝置 Pocket Sewing

在褲袋邊緣車上包邊布條，以強化縫合處並增加美觀。

喇叭PS201:可用布條寬度為3/8" (9.5mm)

Overlock sewing with tape binding for strengthening the pocket edge.

PS201: Folder, for tape width 3/8" (9.5mm)

可自行組裝 self-installation : YES

適用機型 applicable model : 757L-516M-3



## UC

### 上下層防捲邊 Top and Bottom Anti-Curly Edge

針對易捲曲布料所開發的氣動裝置，在布料進入壓腳之前，將布料吹平，適用內捲，外捲等各種捲曲的情形，大幅增加車縫效率。

有三種版本可選搭: UC-LD(高級電控式) · UC-L2(經濟機械式) · UC-L3(外捲單一式)

The pneumatic device solves the problem of curly edge material. The fabric edge is flattened by air before entering the presser foot. Applicable to up-roll, down-roll, and all kinds of curly edge situations, which highly improves the sewing efficiency.

There are 3 types for this device. UC-L (High-end electronic control type), UC-L2 (economic mechanical type), and UC-L3 (Up-roll only type).

▲高級電控式  
High-end electronic control type



▲機械式  
Mechanical type




可自行組裝 self-installation : YES  
適用機型 applicable model : 700L Series




▲UC-LD




▲UC-L2/UC-L3




▲外捲模式 Up-roll :  
UC-L2/UC-L3 Mechanical  
& Automatic-Type



▲內捲模式 Down-roll :  
UC-L2 Mechanical  
& Automatic-Type



▲內外捲模式 Up-roll and Down-roll :  
UC Automatic-Type



## TA

### 雙勾針環縫口袋包邊縫合裝置 Two Chainstitch Pocket Sewing Device

在褲袋邊加包邊布條並車兩道環縫線，以強化縫合處增加美觀。

標準喇叭(入布寬度25.4mm/出布寬度6.4mm)

Tape binding by two chainstitch sewing for strengthening the pocket edge.

Standard folder(tape width 25.4mm/ finish width 6.4mm)

可自行組裝 self-installation : YES  
適用機型 applicable model : 757L-401M



## TB-K1

### 全沉式機頭安裝支撐組 Machine Body Supporter for Full Submerged Table

全沉式桌板機頭支撐組。

700K series machine base for full submerged table.

可自行組裝 self-installation : YES  
適用桌板 applicable model : Table 700K-T2, 700K-T3



## TG

### 車肩帶裝置 Tape Guide

在車針織布時多車上一條平織布條，可防止肩部寬變型張開，壓具P254J-4A布條最大寬度為13mm。

To prevent knit wear shoulder stretching, insert woven tape for strengthening.  
P254J-4A: Presser foot for maximum tape width is 13 mm.

可自行組裝 self-installation : YES  
適用機型 applicable model : 747L-514M-3, 747L-514H-4



**VT**

**側吸式切線裝置 Side Suction Thread Chain Cutter Device**

利用吸風馬達或空壓機將線吸入切刀槽中予以切斷(較適用於3~4線之機型)。  
Take thread into trimmer tube by suction motor or air compressor. (Applicable for 3-4 thread machine)

可自行組裝 self-installation : YES  
適用機型 applicable model : 737L, 747L, 737KS, 747KS



**VTE  
VTE-U**

**側吸式自動切線裝置 (附電眼節能裝置)  
Side Suction Auto Thread Chain Cutter Device (with Sensor-controlled Energy-saving Device)**

電控系統支持電眼節能裝置，採用電眼偵測布邊，利用控制箱調整旋鈕，控制吸風功能在切線時運作，減少空壓設備的能源消耗，並避免縫線浪費。

Our computerized system drives sensor-controlled energy saving device. Sensor checks the fabric edge. Turn the button of control box to set the time of air suction of chain-cutter. It saves the energy consuming of air compressor system and also saves thread consuming.

	前/中電眼 Front/middle sensors	抬壓腳 Foot Lifter	氣動配件Pneumatic Set	
			吸風集塵組 Suction Set	吸風線槽 Suction Channel
VTE	V	氣動 Pneumatic	V	V
VTE-U	V	氣動 Pneumatic	V	V

可自行組裝 self-installation : NO  
適用機型 applicable model : 737L, 747L



**WR/  
LFC-3**

**管狀布條車縫裝置(反條裝置) Spaghetti Sewing**

針織布條之拷邊車縫並反條成管形，適用於各種泳衣或睡衣、韻律服等管形肩帶，喇叭布條寬度約22.2mm (7/8")，成型肩帶直徑5mm。

Overlock sewing at knit tape edge and then turn it into tube. For swimwears, night gowns etc. Folder size: tape width is 22.2mm, finished tube size is 5mm in diameter.

可自行組裝 self-installation : YES  
適用機型 applicable model : 737L

**TUA-3X**

**三合一吸風集塵組 / 3-in-1 Dust Collecting Suction Device**

電眼機型(ECA, ECB, CTE, VTE)標準配備的吸風集塵組，適用於700L、700KT/ KS/KST系列，線屑(後吸風)、布屑(前吸風)、棉絮(內吸風)同時清除。


Standard device of sensor-controlled machine (ECA, ECB, CTE, VTE), which cleans away thread ends (rear suction), cloth waste (front suction), and lint (inner suction). Compatible to 700L, 700KT/KS/KST.

代號 Code	功能組件 Functional Section					適用機型 Applicable Series	備註 Remark		
	●吸布屑方式 Vacuuming Way		●拾壓腳 Presser Foot Lifter	●附加功能 Additional Features	氣閥 Air Switch			濾瓶 Filter	
	前吸/後吸 Front/Back	切刀驅動 Trimmer			機械式 Mechanical Type				電磁閥式* Solenoid Type
TUA-31	●			單聯 Single way		●	700K / L KS / KST / KT	700K / Q 腳踏連桿共用 The treadle rod of 700K / Q is shared.	
TUA-31-A									
TUA-32K	●			雙聯 Double ways			700K / L / KS / KST / KT		
TUA-33K	●				單聯 Single way	●	700K	電控型號：HD40-2-7K Control box model: HD40-2-7K	
TUA-34K		●			雙聯 Double ways	●		電控型號：HD40-2-7K Control box model: HD40-2-7K	
TUA-32KT	●			雙聯 Double ways			700KT	電控型號：HD40-2-7K Control box model: HD40-2-7K	
TUA-34KT		●			雙聯 Double ways	●		電控型號：HD40-2-7K Control box model: HD40-2-7K	
TUA-36	不零售，700LD專用CTE,ECA,ECB,VTE,VTA (搭配電眼節能省風裝置) No retail, exclusive CTE, ECA, ECB, VTE, VTA for 700LD (Allocated with the electronic eye, power-and-wind-saved device)								
TUA-37S					單聯 Single way	●	700KS	電控型號：HD40-2-7K Control box model: HD40-2-7K	
TUA-38S	●				雙聯 Double ways	●		電控型號：HD40-2-7K *僅適用700KS Control box model: HD40-2-7K *only for 700KS	
TUA-39S				單聯 Single way					
TUA-40S		●		雙聯 Double ways				*僅適用700KS *only for 700KS	
TUA-38ST	●				雙聯 Double ways	●	700KST	電控型號：HD40-2-7K *僅適用700KST Control box model: HD40-2-7K *only for 700KST	
TUA-40ST		●		雙聯 Double ways				*僅適用700KST *only for 700KST	
TUA-41ST	●		●撥桿感測裝置 The alignment device		三聯 Trigeminy	●	700KS / RSK	電控型號：i60S-7-RS-220 *僅適用700KS/RSK 接頭規格 *包含電眼控制過骨機構彈開功能 Control box model: i60S-7-RS-220 *only for 700KST *with sensor-controlled flick function for cross seam mechanism	
代號 Code	功能組件 Functional Section					適用機型 Applicable Series	備註 Remark		
	●吸布屑方式 Vacuuming Way		●拾壓腳 Presser Foot Lifter	●附加功能 Additional Features	氣閥 Air Switch			濾瓶 Filter	
	前吸/後吸 Front/Back	切刀驅動 Trimmer			電磁閥式* Solenoid Type				
TUC-01		●	●		三聯 Trigeminy		700K / L	ECA-U 機型用 For ECA-U	
TUC-02					單聯 Single way			ECB-U 機型用 For ECB-U	
TUC-03				●鬆線 Thread Release	三聯 Trigeminy		700K / L	VTE-U 機型用 For VTE-U	
TUC-04					雙聯 Double ways			CTE-U 機型用 FOR CTE-U	
TUC-05	●		●		雙聯 Double ways	●	700L	VT 機型用 *僅適用 DKU501ADE 電控箱 FOR VT *Only applicable to electric control box DKU501ADE	
TUC-05-A					雙聯 Double ways			*拾壓腳汽缸組EC415U-A *僅適用 DKU501ADE 電控箱 *cylinder group with presser foot EC415U-A *Only applicable to electric control box DKU501ADE	
TUC-08				●鬆線 Thread Release	三聯 Trigeminy		700KQ	VTE-Q 機型用 For VTE-Q	
TUC-09					單聯 Single way		700L	無拾壓腳僅前後吸風 *僅適用 DKU501ADE 電控箱 No presser foot lifter, only front and back vacuuming *Only applicable to electric control box DKU501ADE	

\*TUA-37S、TUA38S、TUA39S、TUA40S、TUA-38ST、TUA40ST、TUA41S、TUA41ST 需搭配開口型桌板(70頁) Open type table required (Page.70)

\*備註: 電磁閥需由伺服馬達的電控箱驅動, 接頭規格15-Pin(賀欣系列)·TSA或簡易直驅系列不支援

\* Remark: The solenoid must be driven by full function servo motor. The adapter spec is 15-Pin (Hohsing series). TSA Series and Simple type direct drive servo motor are not applicable.



# TABLE

桌板代號 Item No.	尺寸 / Size (mm)			說明 Description	適用機型 Applicable Model	備註 Remark
	長 Length	寬 Width	厚 Thickness			
700K-T	1200	540	40	② 半沉式 Semi-submerged	700L, 700KT 一般車 700L, 700KT Standard Model	
700K-T2	1200	540	40	① 全沉式 Fully-submerged	700L 一般車 700L Standard Model	需搭配 TB-K1 TB-K1 set required
700K-T3	1200	540	40	① 全沉式 Fully-submerged	700L/EC, CT, VT	需搭配 TB-K1 TB-K1 set required
700K-T4	1200	540	40	② 半沉式 Semi-submerged	700L/BKF1	
700LD-T	1200	540	40	② 半沉式 Semi-submerged	700KT, 700L 直驅車 700KT, 700L DD Motor Model	
700LD-T1	1200	540	40	② 半沉式 Semi-submerged	700LD/UC	
700KS-T	1200	540	40	② 半沉式 Semi-submerged	700KS, 700KST	
700KS-T2	1200	540	40	② 半沉式 Semi-submerged	700KS, 700KST 直驅車 700KS, 700KST DD Motor Model	
700KS-T1	1200	540	40	② 半沉式 Semi-submerged	700KS, 700KST	開口型 Open type
700KS-T3	1200	540	40	② 半沉式 Semi-submerged	700KS, 700KST 直驅車 700KS, 700KST DD Motor Model	開口型 Open type
700KS-T4	1200	540	40	② 半沉式 Semi-submerged	700KS, 700KST	開口型搭 KX10E-A布漏組 Open type with KX10E-A cloth slide
700KS-T5	1200	590	40	③ 上乘式 Non-submerged	700KS/LFD	開口型 · 搭SM899-A Open type with SM899-A